Material Safety Data Sheet

MSDS

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

Standard must be consulted for specific requirements.

Chemical Name: XPEL Application Gel 2.0

Date of Preparation: 11/19/2010

Section 1 – Chemical Product and Company Identification

Product / Chemical Name: XPEL Application Gel Manufactuer's Name: XPEL Technologies Corp.

Address: 618 W. Sunset Rd.

San Antonio, TX 78216

CAS NumberPaint Protection Film Installation

General Use

Emergency Telephone Number: 800-424-9300

Telephone Number for Information: 800-447-9928

Date Prepared: 11/19/2010

Section 2 – Composition / Information on Ingredients

Hazardous Components (Specific Chemical Identity; Common Names(s))

OSHA PEL ACGIH CAS# (optional)

Isopropanol 400 ppm 400 ppm 67-63-0 <5

Section 3 - Hazards Identification

Emergency Overview



Potential Health Effects

Eye Contact: May cause eye irritation.

Skin Contact: No irritation or reaction expected.

Inhalation: Not applicable.

Ingestion: May cause upset stomach, nausea (Abnormal entry route). Carcinogenicity: Not listed as a carcinogen by NTP, IARC, OSHA or ACGIH.

Section 4 – First Aid Measures

Eye Contact: Do not rub eyes. Flush eyes thoroughly with water for 15 minutes. If

condition worsens or irritation persists, contact physician.

Skin Contact: Not applicable. Inhalation: Not applicable.

Ingestion: Do not induce vomiting. Contact a physician or Poison Control Center.

Section 5 – Fire-Fighting Measures

Flash Point: Non-flammable **Autoignition Temperature:** N/A

LEL: N/A UEL: N/A

Flammable Limits: N/A
Extinguishing Media: N/A

Unusual Fire or Explosion Hazards: N/A Hazardous Combustion Products: N/A

Fire-Fighting Instructions: N/A **Fire-Fighting Equipment:** N/A

Section 6 - Accidental Release Measures

Spill / Leak Procedures: Small spills can be flushed down the drain. Large spills should be contained and collected for disposal. Floor may be slippery - use care to avoid falls. Remove contaminated clothing and wash before reuse.

Waste Disposal Method: Liquid wastes are not permitted in landfills. Usable liquid may be absorbed on an inert absorbent material, drummed, and taken to a chemical or industrial incineration facility. Reclaim larger spills if feasible. Consult local, state, and federal regulations for proper disposal in your area.

RCRA Hazardous Waste Numbers: N/A

Section 7 - Handling and Storage

Storage Requirements: Avoid freezing conditions

Section 8 – Exposure Controls / Personal Protection

Eye Protection: None required under normal conditions. **Skin Protection:** None required under normal conditions.

Respiratory Protection: None required under normal conditions.

Ventilation: None required under normal conditions.

Protective Equipment or Clothing: None required under normal conditions.

Section 9 - Physical and Chemical Properties

Appearance and Odor: A colorless, slightly viscous liquid with

no odor.

Vapor Pressure: Not Determined Vapor Density (Air=1): 1:2 Specific Gravity: 1.0102 Water Solubility: 100% Melting Point: 32° F

Boiling Point: Not Determined

% Volatile: 0.0067%

Evaporation Rate (n-BuAc=1): <1

Section 10 – Stability and Reactivity

Stable/non-reactive product

Section 11 – Toxicological Information

No acute or chronic toxic effects expected when used according to directions.

Section 12 - Ecological Information

No ecological or special considerations when used according to directions. Not considered environmentally harmful from normal dilution, expected usage and typical drainage to sewers, septic systems and treatment plants.

Section 13 – Disposal Considerations

Dispose according to local, state and Federal regulations.

Section 14 – Transport Information

DOT Proper Shipping Name: NONE

DOT Class: N/A

TSCA Chemical Inventory: No ingredients are listed

CWA 40 CFR Part 117 Substance: None

PIN: N/A

DOT Label: None

Notice: The information herein is based on data considered to be accurate as of the date of preparation of this material safety data sheet. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information. The user assumes all liability for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices or from any hazards inherent in the nature of the product.